

ETHICHECK LTD

Unit 5B Blacknest Industrial Estate, Bentley, Hampshire, UK Phone: +44 (0) 1372 236 455 Fax: +44 (0) 1372 464 545 Email: info@ethicheck.eu www.ethicheck.eu

The Matos® Plus Eco fridge series is a new range of purpose built Medical and Vaccination Refrigerators utilising patented technology. The cabinet and componentry have been specially designed for use in the Medical field.

Model Variations

Eco 1460 R – Solid Door Eco 1460 R/G – Glass Door

Eco 1460 R/D – Solid Door, hot gas defrost Eco 1460 R/GD – Glass Door, hot gas defrost



Interior Finish

All Matos[®] Plus Eco fridges come with a high quality aluminium interior and use polyurethane foam thermal insulation. A stainless steel interior is also offered as an option.

Lock Fitted as Standard

Maintains security and ensures the unit can only be opened by authorised personnel.

Solid or Glass Door Options

Most models come with solid or glass door options enabling you to select the format which best suits your requirements.

Auto Defrost

The advanced controller initializes a regular defrost sequence to decrease the chance of ice build-up while maintaining the temperature below 8°C. Matos° Plus Eco fridges can also be ordered with a gas defrost capability.

Energy Efficient

Matos[®] Plus Eco fridges are more energy efficient and kinder to the environment, meaning the running costs of the refrigerator are kept as low as possible.

5 Year Extended Warranty

When serviced by an approved service technician, the warranty is extended to 5 years - Parts Only.

Specifications

Capacity	1460L	Power	550W
Dimensions External	1450w x 1970h x 950d	Air convection	Forced Air
Dimensions Internal	1340w x 1460h x 750d	Temperature range	0°C – +15°C
Max shelf workload	30kg	Controller	Microprocessor with external LCD graphic display
Max unit workload	300kg	Interior	Aluminium (s/steel optional)
Door	Solid/Glass option	Housing	Powder coated sheet (s/steel optional)
Weight	200kg	Temperature resolution	0.1°C
Shelves fit/max	2 x 3/11	Temperature fluctuation at 4°C	+/- 0.5°C
Gas defrost	Optional	Voltage 50/60Hz	115/230V
Refrigerant	R290	Internal light	Yes
Refrigerant amount	60 grams	Door Open Alarm	Yes
Castors	Yes	Access port	Yes