

ETHICHECK LTD

Unit 5B Blacknest Industrial Estate, Bentley, Hampshire, UK
 Phone: +44 (0) 1372 236 455 Fax: +44 (0) 1372 464 545
 Email: info@ethicheck.eu www.ethicheck.eu

Model Variations

Eco 150 S – Solid Door

Eco 150 S/G – Glass Door



MATOS Eco 150 S/G

The Matos® Plus Eco Cooled Incubators are a new range of purpose built Medical Chambers utilising patented technology. The cabinet and componentry have been specially designed for use in the Medical field.

Interior Finish

All Matos® Plus Eco Cooled Incubators come with a high quality aluminium interior and use polyurethane foam thermal insulation. A stainless steel interior is also offered as an option.

Lock Fitted as Standard

Maintains security and ensures the unit can only be opened by authorised personnel.

Solid or Glass Door Options

Most models come with solid or glass door options enabling you to select the format which best suits your requirements.

Auto Defrost

The advanced controller initializes a regular defrost sequence to decrease the chance of ice build-up while maintaining the temperature.

Energy Efficient

Matos® Plus Eco Cooled Incubators are more energy efficient and kinder to the environment, meaning the running costs of the refrigerator are kept as low as possible.

5 Year Extended Warranty

When serviced by an approved service technician, the warranty is extended to 5 years - Parts Only.

Specifications

Capacity	150L	Power	170W
Dimensions External	620w x 860h x 650d	Air convection	Forced Air
Dimensions Internal	520w x 660h x 420d	Temperature range	+3°C – +40°C
Max shelf workload	10kg	Controller	Microprocessor with external LCD graphic display
Max unit workload	30kg	Interior	Aluminium (s/steel optional)
Door	Solid/Glass option	Housing	Powder coated sheet (s/steel optional)
Weight	54kg	Temperature resolution	0.1°C
Shelves fit/max	3/4	Temperature fluctuation at 4°C	+/- 0.5°C
Gas defrost	Optional	Voltage 50/60Hz	115/230V
Refrigerant	R134A	Door Open Alarm	Yes
Refrigerant amount	0.065kg	Access Port	Yes
Castors	Optional	Internal light	Yes